

GENERAL INSTRUCTIONS FOR KLEEN KOTE™ 111 BOND BREAKER

REV. 022513

General Instructions for KLEEN KOTE™ 111 Bond Breaker

Call (800) 801.7832 or visit www.4progressive.com for further information, detailed instructions, MSD sheets or special assistance.

IF YOU HAVE NOT USED THIS PRODUCT PREVIOUSLY, PLEASE CALL TECHNICAL SUPPORT PRIOR TO USE.

SURFACE/EQUIPMENT PREPARATION

Clean all application equipment and dispensing containers prior to using/dispensing KLEEN KOTE. Do NOT mix with other bond breakers or release agents. The application surface must be clean prior to use. Sweep down the entire floor before applying KLEEN KOTE. DO NOT apply KLEEN KOTE over puddles of standing water or debris. When setting rebar, make sure to keep the formed area clean and free of debris and other chemicals.

APPLICATION

Floor Application: KLEEN KOTE may be applied at any time prior to the pour. Spray KK 111 Bond Breaker in a crossing pattern. Spray entire floor wet in one direction. Then spray the entire floor wet 90° from the direction originally sprayed. KK 111 Bond Breaker may be applied over floor sealers that are FULLY CURED. Allow KK 111 Bond Breaker to turn from white to clear. Once it turns clear it will not leave a shine or film on the surface and will not rinse off in the rain, but CANNOT be applied in the rain. Form Application: Set up your forms and spray with KK 111 Bond Breaker. Allow the product to turn from white to clear. Proceed with your pour as normal.

COVERAGE RATES

1 gallon (3.78 liters) of KLEEN KOTE will cover approx. 2,000 sq. feet (185 sq. meters) depending on the surface type being treated. Spray on for best performance and ease of application.

IMPORTANT INFORMATION

Never dispense KLEEN KOTE in a drum or container previously used to store acid. Do not use an applicator or sprayer used for acid. The acid residue cannot be removed and will cause KLEEN KOTE to separate. KLEEN KOTE can NOT be used in most stack casting situations unless concrete is cured for greater than 30 days.

PREVENT KLEEN KOTE FROM FREEZING!

DO NOT MIX WITH OTHER RELEASE AGENTS OR CHEMICALS!

IMPORTANT: PROPER VIBRATION ENSURES THE HIGHEST PANEL QUALITY. DRAGGING VIBRATORS OR TOUCHING VIBRATORS TO THE CASTING BED WILL CAUSE SPOT STICKAGE. CALL OR VISIT OUR WEBSITE FOR SPECIFIC VIBRATION INSTRUCTIONS.

FIRST AID PROCEDURES

If contact with eyes occurs, immediately flush with water. If swallowed, do NOT induce vomiting. In either case seek medical attention immediately. Additional information is available on the MSD sheet.

WARNINGS

Please keep this and all chemicals out of reach of children! Use this product only as directed. Non-stick products may cause slipperiness on surfaces.