

KLEEN KOTE™ - AGRICULTURE AND HAULING EQUIPMENT INSTRUCTIONS

REV. 05.30.13

Use KLEEN KOTE™ 300 on hauling equipment. mower decks, hoppers, manure spreaders and combines to keep mud, debris, agricultural products, snow, salt and ice from sticking. It is an environmentally safe alternative to traditional release agents, diesels or other fuels. It also provides rust-inhibiting qualities to help prevent corrosion.

RATIOS (MIX KLEEN KOTE™ TO WATER)

Mix Ratio 1 to 8 thru 1 to 11 -- Depending Upon Results

TYPICAL COVERAGE RATES

1 gallon of mixed KLEEN KOTE™ will cover approx. 2000 square feet (185 sq. meters), depending on the surface type. Spray on for best performance and ease of application.

1. DETERMINE YOUR MIX RATIO

Please see the above starting mix ratios. Ratios can be adjusted based upon your results. They may be adjusted up or down in one part increments to achieve optimum results. **NOTE:** The more concentrate you add the thicker and more protective KLEEN KOTE™ will be.

2. MIXING

Using a clean container, add KLEEN KOTE™ and water to achieve the recommended ratio for your application. Adding KLEEN KOTE™ to water and then adding more water will eliminate the need for mixing. Do **NOT** mix with diesel, fuels or oils. Do **NOT** mix with other release agents or chemicals.

3. APPLICATION

KLEEN KOTE™ may be applied at any time. For best results, the application surface should be cleaned prior to application. Remove all other release agents and chemicals before applying KLEEN KOTE™.

4. SPRAYING

Spray on and then let change from white to clear before using the treated equipment. If KLEEN KOTE™ freezes on the surface you are treating, it will still work for certain applications. Reapply after every use.

TIPS FOR USE

- Remove all previous release agents or coatings from the equipment prior to applying KLEEN KOTE™ to eliminate any adverse reaction between KLEEN KOTE™ and the previous coating.
- For debris, agricultural products, mud and snow hauling, spray KLEEN KOTE™ once a day prior to your first use. In freezing weather, the bed or equipment must be warmed indoors prior to applying KLEEN KOTE™.
- KLEEN KOTE™ must turn from white to clear after it is sprayed on the bed before you start hauling.
- If you wash the equipment with soap and water, you must re-apply KLEEN KOTE™ before hauling your next load.

NOTES

- DO NOT switch back and forth between KLEEN KOTE™ and other release agents due to possible incompatibilities.
- You do not have to wait for the bed or equipment to dry after cleaning. KLEEN KOTE™ may be applied directly to a wet bed or equipment.
- KLEEN KOTE™ can be applied as a polish to the cab to keep debris, agricultural product, mud, salt or snow from sticking to the surface. See Antique Farming Equipment Instructions for details on applying to the cab.
- KLEEN KOTE™ may also be applied to the wheels and undercarriage to keep debris, agricultural products, mud, salt and snow from sticking.
- In freezing weather, mix product as needed. Concentrate will not freeze however premix may freeze.

If you have any questions regarding the use of this product please feel free to contact Customer Support