

KLEEN KOTE USAGE GUIDE

Quantities provided below are estimated on a per hold basis.

Cargo	Mix Ratio	Handymax	Panamax
Green Delay Petcoke (GDP) Sulfur	3 to1	Use 54 ltrs. of concentrate to 162 ltrs. of fresh water CONCENTRATE NEEDED PER HOLD 3 - 17.9 ltr. Pails OR 54 ltrs. of 208 ltr. Drum	Use 71 ltrs. of concentrate to 216 ltrs. of fresh water CONCENTRATE NEEDED PER HOLD 4 - 17.9 ltr. Pails OR 71 ltrs. of 208 ltr. Drum
Coal Fertilizer Petcoke Salt	5 to1	Use 36 ltrs. of concentrate to 180 ltrs. of fresh water CONCENTRATE NEEDED PER HOLD 2 - 17.9 ltr. Pails OR 36 ltrs. of 208 ltr. Drum	Use 54 ltrs. of concentrate to 270 ltrs. of fresh water CONCENTRATE NEEDED PER HOLD 3 - 17.9 ltr. Pails OR 54 ltrs. of 208 ltr. Drum
Boxite Cement Clinker Sugar	10 to1	Use 18 ltrs. of concentrate to 198 ltrs. of fresh water CONCENTRATE NEEDED PER HOLD 1 - 17.9 ltr. Pail OR 18 ltrs. of 208 ltr. Drum	Use 36 ltrs. of concentrate to 377 Ltrs. of fresh water CONCENTRATE NEEDED PER HOLD 2 - 17.9 Ltr Pails OR 36 ltrs. of 208 ltr. Drum

Mix ratios are water to Kleen Kote. Ratios can be adjusted up or down based upon your results. Average coverage rate per liter is 47 sq. mtrs. Coverage rates depend heavily on application equipment and hold paint conditions. Rusted and pitted walls or tank tops will require additional product.